

高速光耦

High Speed Photo Coupler

HLW501 HLW511

High Speed 1MBit/s Logic Gate

概述 Description

HLW501、HLW511 是一种用于单通道的高速光耦合器，由一个 850nm 的 AlGaAs LED 光学耦合到一个高速光电探测器组成。光电二极管偏极和输出晶体管集电极的单独连接，可以通过降低基极集电极电容，使速度比传统光电晶体管耦合器提高 100 倍。

HLW501, HLW511 are high-speed optical couplers for single channel, consisting of an 850nm AlGaAs LED optically coupled to a high-speed photodetector. A separate connection between the photodiode polarizer and the output transistor collector allows speeds to be 100 times higher than conventional phototransistor couplers by reducing the base collector capacitance.

特性 Features

- 高比特率: 1MBit/s
High speed – 1 MBit/s
- 输入和输出之间的高隔离电压($V_{iso}=3750\text{ V rms}$)
High isolation voltage between input and output ($V_{iso}=3750\text{ V rms}$)
- 兼容 TTL
TTL Compatible
- 集电极开路输出
Open-Collector Output
- 符合安规标准: UL 1577, VDE DIN EN60747-5-5 (VDE 0884-5), CQC11-471543-2022
Meet Safety standard : UL 1577, VDE DIN EN60747-5-5 (VDE 0884-5), CQC11-471543-2022


应用 Applications

- CMOS-LSTTL-TTL 的输出接口
Output interface to CMOS-LSTTL-TTL
- 通信设备
Telecommunication equipment
- 电机驱动中的功率晶体管隔离
Power transistor isolation in motor drives
- 替代低速光电晶体管光电耦合器
Replacement for low speed phototransistor photocouplers


真值表 Truth table

LED	VO
OFF	H
ON	L

封装和原理图 Package and Schematic Diagram




SOP6-W



SOP6-P

注: 在引脚 4 和 6 之间必须连接一个 0.1uF 的旁路电容器。

Note: 0.1uF bypass capacitor must be connected between pins 4 and 6.



Pin Configuration

1. Anode
2. NC
3. Cathode
4. GND
5. VO
6. VCC

Beijing Hongli Kunpeng International Trade Co., Ltd.

Tel: 86-10-57891098 MP:86-13001179378 Mail: info@hllkpint.com or lucyliu0807@163.com

产品型号命名规则 Order Code

HL W5XX - UN Y - W (V) (ZZ)

① ② ③ ④ ⑤ ⑥ ⑦

- ① 公司代码 Company Code (HL: 鸿利鲲鹏 Hongli Kunpeng)
- ② 产品系列 Product Series (XX: 01, 11)
- ③ 框架类型 Lead Frame (Cu: 铜框架 Copper)
- ④ 树脂类型 Epoxy Type (H: 无卤 Halogen-free)
- ⑤ 封装形式 Package (S: SOP)
- ⑥ 器件工作温度范围 Device Operating Temperature Range (特殊范围需填或者空白 Special Range need to be filled in or left blank)
- ⑦ 内部补充代码 Internal Supplementary Code (数字或者空白 Number or None)

印字信息 Marking Information

- 印字中的“XX”代表产品分档: 01、11
“XX”denotes the classification: 01、11
- 印字中“Y”代表年份; A(2018),B(2019),C(2020).....
“Y”denotes YEAR: A(2018), B(2019), C(2020).....
- 印字中“WW”代表周号
“WW”denotes week's number
- 印字中“N”代表星期几
“N”denotes the day of the week
- 印字中的“H”代表无卤
“H”denotes Halogen-free



绝缘和安规信息 Insulation and Safety related specifications

项目 Item	符号 Symbol	数值 Value	单位 Unit	备注 Remark
爬电距离 Creepage Distance	L	> 8.0	mm	从输入端到输出端，沿本体最短距离路径 Measured from input terminals to output terminals, shortest distance path along body
电气间隙 Clearance Distance	L	> 8.0	mm	从输入端到输出端，通过空气的最短距离 Measured from input terminals to output terminals, shortest distance through air
绝缘距离 Insulation Thickness	DTI	> 0.4	mm	发射器和探测器之间的绝缘厚度 Insulation thickness between emitter and detector
峰值隔离电压 Peak Isolation Voltage	V_{IORM}	600	V_{peak}	DIN/EN/DIN EN60747-5-5
瞬态隔离电压 Transient isolation voltage	V_{IOTM}	5000	V_{peak}	DIN/EN/DIN EN60747-5-5
隔离电压 Isolation Voltage	V_{iso}	> 3750	V_{rms}	For 1 min

极限参数 Absolute Maximum Ratings ($T_a=25^{\circ}C$)

参数 Parameter		符号 Symbol	额定值 Rating	单位 Unit
发射端 Input	正向电流(平均) DC/Average Forward Input Current	$I_{F(av)}$	25	mA
	正向峰值电流 (50%占空比, 1ms p.w.) Peak forward input current (50% duty cycle, 1 ms p.w.)	$I_{F(pk)}$	50	mA
	反向电压 Reverse Input Voltage	V_R	5.0	V
	正向瞬态峰值电流 ($\leq 1\mu s$ p.w., 300pps) Peak transient input current ($\leq 1\mu s$ p.w., 300 pps)	$I_{F(trans)}$	1	A
	输入功耗 Input Power Dissipation	P_I	45	mW
接收端 output	电源电压 Supply Voltage	V_{CC}	-0.5 ~ 30	V
	输出电流 Output Current	I_O	8	mA
	输出电流峰值 Peak output current	$I_{O(pk)}$	16	mA
	输出集电极功耗 Output Collector power dissipation	P_O	100	mW
	输出电压 Output Voltage	V_O	-0.5 to 20	V
工作温度 Operating Temperature	T_{opr}	-40~+85	$^{\circ}C$	
存储温度 Storage Temperature	T_{stg}	-55~+125	$^{\circ}C$	
焊接温度 Soldering Temperature	T_{sol}	260	$^{\circ}C$	

Beijing Hongli Kunpeng International Trade Co., Ltd.

Tel: 86-10-57891098 MP:86-13001179378 Mail: info@hlkpint.com or lucyliu0807@163.com

高速光耦

HLW501 HLW511

High Speed Photo Coupler

High Speed 1MBit/s Logic Gate

推荐操作条件 Recommended Operating Conditions

参数 Parameter	符号 Symbol	最小值 Min	最大值 Max.	单位 Unit
电源电压 Power Supply Voltage	V_{CC}	4.5	18	V
开启电流 Forward Input Current (ON)	$I_{F(ON)}$	2	20.0	mA
关断电压 Forward Input Voltage (OFF)	$V_{F(OFF)}$	0	1.2	V
操作温度 Operating Temperature	T_A	-40	85	°C

Beijing Hongli Kunpeng International Trade Co., Ltd.

Tel: 86-10-57891098 MP:86-13001179378 Mail: info@hlkpint.com or lucyliu0807@163.com

高速光耦

HLW501 HLW511

High Speed Photo Coupler

High Speed 1MBit/s Logic Gate

产品特性参数 Electro-optical Characteristics (Ta=25°C)

参数 Parameter		符号 Symbol	条件 Condition	最小 Min.	典型 Typ.	最大 Max.	单位 Unit
发射端 Input	正向电压 Forward Voltage	V_F	$I_F=16mA$	-	1.45	1.7	V
	反向击穿电压 Reverse Breakdown Voltage	B_{VR}	$I_R=10\mu A$	5	20	-	V
	正向电压温度系数 Diode Temperature Coefficient	$\Delta V_F/\Delta T_A$	$I_F=10mA$	-	-1.6	-	mV/°C
	高电平电源电流 High Level Supply Current	I_{CCH}	$V_{CC}=15V$ $I_F=0mA$ $V_O=Open$	-	-	1	μA
接收端 Output			$T_A=0-70^\circ C$	-	-	2	μA
	低电平电源电流 Low Level Supply Current	I_{CCL}	$V_{CC}=15V$ $I_F=16mA$ $V_O=Open$	-	120	800	μA
传输特性 Transfer Characteristics	高电平输出电流 HIGH Level Output Current	I_{OH}	$I_F=0mA$ $V_O=V_{CC}=5.5V$	-	0.001	0.5	μA
			$I_F=0mA$ $V_O=V_{CC}=15V$	-	0.005	1	
			$T_A=0-70^\circ C$	-	-	50	
	低电平输出电压 LOW Level Output Voltage	V_{OL}	$I_F=16mA$ $V_{CC}=4.5V$ $I_O=3.0mA$	-	0.1	0.4	V
			$I_F=16mA$ $V_{CC}=4.5V$ $I_O=2.4mA$	-	0.1	0.5	V
	电流传输比 Current transfer ratio	CTR	$I_F=16mA$ $V_{CC}=4.5V$ $V_O=0.4V$	19	-	-	%
$I_F=16mA$ $V_{CC}=4.5V$ $V_O=0.5V$			15	-	-		
隔离电压 Isolation Voltage	V_{ISO}	$RH<50\%$ $T_A=25^\circ C$ $I_{I-O}\leq 50\mu A$	3750	-	-	VRMS	
隔离电阻 Resistance (Input to Output)	R_{I-O}	$V_{I-O}=500V$	-	10^{12}	-	Ω	
隔离电容 Capacitance (Input to Output)	C_{I-O}	$f=1MHz$	-	0.6	-	pF	

Beijing Hongli Kunpeng International Trade Co., Ltd.

Tel: 86-10-57891098 MP:86-13001179378 Mail: info@hlpint.com or lucyliu0807@163.com

开关特性 Switching Specification

参数 Parameter	符号 Symbol	条件 Condition	最小 Min.	典型 Typ.	最大 Max.	单位 Unit	
输出高电平传播延迟时间 Propagation Delay Time to Output HIGH Level	T_{PLH}	$I_F=16mA$ $R_L=1.9k\Omega$ $T_A=25^\circ C$	-	150	800	ns	
		$I_F=16mA$ $R_L=1.9k\Omega$ $T_A=0-100^\circ C$			800		
输出低电平传播延迟时间 Propagation Delay Time to Output Low Level	T_{PHL}	$I_F=16mA$ $R_L=1.9k\Omega$ $T_A=25^\circ C$	-	200	800	ns	
		$I_F=16mA$ $R_L=1.9k\Omega$ $T_A=0-100^\circ C$			800		
逻辑高电平共模瞬态抗扰度 Common Mode Transient Immunity(at Logic High)	M501	$ CM_H $	$T_A=25^\circ C, I_F=0mA$ $ V_{CM} =10V(\text{Peak})$ $C_L=15pF, R_L=1.9K\Omega$	5000	-	-	V/ μs
	M511		$T_A=25^\circ C, I_F=0mA$ $ V_{CM} =1500V(\text{Peak})$ $C_L=15pF, R_L=1.9K\Omega$	15000	-	-	
逻辑低电平共模瞬态抗扰度 Common Mode Transient Immunity (at Logic Low)	M501	$ CM_L $	$T_A=25^\circ C, I_F=16mA$ $ V_{CM} =10V(\text{Peak})$ $C_L=15pF, R_L=1.9K\Omega$	5000	-	-	V/ μs
	M511		$T_A=25^\circ C, I_F=16mA$ $ V_{CM} =1500V(\text{Peak})$ $C_L=15pF, R_L=1.9K\Omega$	15000	-	-	

典型光电特性曲线 Typical Electro-Optical Characteristics Curves

Fig.1 Normalized CTR vs. Input current




Fig.2 Normalized CTR vs. Ambient temperature




Fig.3 Output current vs. Output voltage




Fig.4 High level output current vs. Ambient temperature




Fig.5 Propagation delay vs. Ambient temperature





Fig.6 Propagation delay vs. Load resistance



Beijing Hongli Kunpeng International Trade Co., Ltd.

Tel: 86-10-57891098 MP:86-13001179378 Mail: info@hlkpint.com or lucyliu0807@163.com



高速光耦

High Speed Photo Coupler

HLW501 HLW511

High Speed 1MBit/s Logic Gate

延迟时间测试电路 Propagation Delay Time Test Circuit



Beijing Hongli Kungpeng International Trade Co., Ltd.

Tel: 86-10-57891098 MP:86-13001179378 Mail: info@hlkpint.com or lucyliu0807@163.com



高速光耦

HLW501 HLW511

High Speed Photo Coupler

High Speed 1MBit/s Logic Gate

CMR 测试电路 Test Circuit for Common Mode Transient Immunity



Beijing Hongli Kungpeng International Trade Co., Ltd.

Tel: 86-10-57891098 MP:86-13001179378 Mail: info@hlkpint.com or lucyliu0807@163.com

高速光耦


HLW501 HLW511

High Speed Photo Coupler


High Speed 1MBit/s Logic Gate

外形尺寸 Outline Dimensions

SOP6-W




SOP6-P



单位 Unit: mm

建议焊盘布局 Recommended Pad Layout



单位 Unit: mm


注：上图为产品正视图。

Note: The picture above is the front view of the product.

Beijing Hongli Kunpeng International Trade Co., Ltd.

Tel: 86-10-57891098 MP:86-13001179378 Mail: info@hlpint.com or lucyliu0807@163.com

回流焊温度曲线图 Solder Reflow Profile




项目 Item	符号 Symbol	最小值 Min.	最大值 Max.	单位 Unit
预热温度 Preheat Temperature	T_s	150	200	$^\circ\text{C}$
预热时间 Preheat Time	t_s	60	120	s
升温速率 Ramp-Up Rate (T_L to T_P)	-	-	3	$^\circ\text{C}/\text{s}$
液相线温度 Liquidus Temperature	T_L	217		$^\circ\text{C}$
时间高于 T_L Time Above T_L	t_L	60	150	s
峰值温度 Peak Temperature	T_P	-	260	$^\circ\text{C}$
T_c 在 $(T_P - 5)$ 和 T_P 之间的时间 Time During Which T_c Is Between $(T_P - 5)$ and T_P	t_p	-	30	s
降温速率 Ramp-down Rate (T_P to T_L)	-	-	6	$^\circ\text{C}/\text{s}$

注 Note:

建议在所示的温度和时间条件下进行回流焊，最多不能超过三次；

Reflow soldering is recommended at the temperatures and times shown, no more than three times;

波峰焊温度曲线图 Wave Soldering Profile



手工烙铁焊接 Soldering with hand soldering iron

A. 手工烙铁焊仅用于产品返修或样品测试;

Hand soldering iron is only used for product rework or sample testing;

B. 手工烙铁焊要求: 温度 $360^{\circ}\text{C} \pm 5^{\circ}\text{C}$, 时间 $\leq 3\text{s}$ 。

Hand soldering iron requirements: Temperature: $360^{\circ}\text{C} \pm 5^{\circ}\text{C}$, within 3s.

高速光耦

HLW501 HLW511

High Speed Photo Coupler

High Speed 1MBit/s Logic Gate


包装 Packing

■ 汇总表 Summary table

封装形式	包装方式	盘数量	盒数量	箱数量	静电袋规格	盒规格	箱(双瓦楞)规格	备注
SOP6	卷盘 (φ330mm 蓝盘)	1千只/盘	2 盘/盒	10 盒/箱	450*390*0.1mm	340*60*340mm	620*360*365mm	首尾端空至少 200mm
Package Type	Packing Form	Quantity per Reel	Quantity per Box	Quantity per Carton	Antistatic Bag Specification	Box Specification	Carton Specification	Note
SOP6	Reel(φ330mm Blue)	1k pcs/reel	2Reel/box	10box/ctn	450*390*0.1mm	340*60*340mm	620*360*365mm	Guard band 200mm min.

■ 编带包装 Tape & Reel

- 1) 每卷数量: 1000 只。
Qty/reel: 1000 pcs.
- 2) 每箱数量: 20000 只。
Qty/ctn: 20000 pcs.
- 3) 内包装: 每卷盘 1000 只。
Inner packing: 1000pcs/reel.
- 4) 示意图 Schematic:



单位 Unit: mm

Beijing Hongli Kunpeng International Trade Co., Ltd.

Tel: 86-10-57891098 MP:86-13001179378 Mail: info@hlkpint.com or lucyliu0807@163.com

注意 Attention

- 鸿利鲲鹏持续不断改进质量、可靠性、功能或设计，保留此文件更改的权利恕不另行通知。
HLKP continuously improve quality, reliability, function and design. We reserve the right to change this document without prior notice.
- 请遵守产品规格书使用，鸿利鲲鹏不对使用时不符合产品规格书条件而导致的质量问题负责。
Please use in accordance with the product specification. HLKP is not responsible for the quality problems caused by non-compliance with the product specifications.
- 对于需要高可靠性或安全性的设备/装置需求，请联系我们的销售人员。
For equipment/devices requiring high reliability or safety, please contact our sales representatives.
- 当需要用于任何“特定”应用时，请咨询我们的销售人员。
When requiring a device for any “specific” application, please contact our sales in advice.
- 如对文件中表述的内容有疑问，欢迎联系我们。
If you have any questions about the contents of the document, please contact us.