

SMD POWER INDUCTORS:

HL0515H Series





110.0

Series	A(mm) B(mm)		C (mm)	D (mm)	E (mm)
HL 0515H	5.3MAX	5.6±0.3	1.5MAX	1.2±0.3	2.0±0.3
Deut Messelver	LO Inductance (µH) ±20%	Heat Rating Current Irms(A)	Saturation Current Isat (A)	DCR(mΩ)	
Part Number				TYP.	MAX.
HL0515H-R22M-P	0.22	13.0	16.0	7.2	8.5
HL0515H-R47M-P	0.47	8.0	12.0	12.0	13.8
HL0515H-R68M-P	0.68	7.0	10.0	15.0	20.0
HL0515H-1R0M-P	1.0	5.0	8.0	28.0	33.0
HL0515H-2R2M-P	2.2	4.0	5.0	60.0	70.0
HL0515H-3R3M-P	3.3	3.0	4.0	75.0	90.0

2.5

3.5

NOTES:

- 1. All test data is referenced to $25^{\circ}\!\mathrm{C}$ ambient
- 2. Operating Temperature Range -55℃ to +150℃
- 3. Irms : DC current (A) that will cause an approximate ΔT of 40 $^{\circ}$ C

4.7

- 4. Isat : DC current (A) that will cause Lo to drop approximately 30%
- 5. Test Frequency: 100KHZ,1.0V


HL0515H-4R7M-P

SMD POWER INDUCTORS:

HL0515H Seri

135.0


Recommend Land Pattern Dimensions (推荐焊盘)




Α	2.50
В	3.00
С	7.00

Unit: mm

Packaging Information (包装信息)



TYPE	A	В	С	D	E	F
12mm	330	100	21.0±0.8	13 ^{+0.5} _{-0.2}	12.0±0.3	18.4



	QTY (PCS)	A0	В0	ко	W	Р	Т
	3000	5.4±0.1	6.0±0.1	1.7±0.1	12.0±0.3	8.0±0.1	0.30±0.05

- ①一卷包装:3000Pcs;
- ① One roll packing :3000Pcs.
- ② 小箱装两卷:一共6000Pcs;
- 2 Small box with two volumes: a total of 6000Pcs
- ③ 大箱装三小箱: 一共18000Pcs.③ Big box three small boxes: a total of 18000Pcs.