



SPECIFICATIONS:

Current Rating: 9A AC,DC
 Voltage Rating: 600V AC,DC
 Temperature Range: -55°C ~ +105°C
 Contact Resistance: 10mΩ Max
 After environmental testing: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Pin Material: Brass/Tin over Nickel
 Material: LCP , UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	4.19	9.40	9P	33.52	38.73
3P	8.38	13.59	10P	37.71	42.92
4P	12.57	17.78	11P	41.90	47.11
5P	16.76	21.97	12P	46.09	51.30
6P	20.95	26.16	13P	50.28	55.49
7P	25.14	30.35	14P	54.47	59.68
8P	29.33	34.54	15P	58.66	63.87

Beijing Hongli Kungpeng International Trade Co., Ltd.

Unit	Scale	Sheet
mm	2:1	1 of 1
Draw BY:	Approved :	
Jack Yin	GONGYB	

Title :
 4.19mm PITCH
 SINGLE ROW WAFER

A0	NEW RELEASE	2015.03.11
REV	DESCRIPTION	DATE

General Tolerance	
x.xx≤0.25	ANGLE±
x.xx≤0.20	
x.xx≤0.15	

DRAW NO :
 HLB-01-WVSB-XP 70

REV
 A1