



SPECIFICATIONS:

Current Rating: 9A AC,DC
 Voltage Rating: 600V AC,DC
 Temperature Range: -55°C ~ +105°C
 Contact Resistance: 10mΩ Max
 After environmental testing: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Pin Material: Brass/Tin over Nickel
 Material: LCP , UL94V-0(Black)

Ordering Information & Dimensions

| Circuits | Dimensions(mm) | | Circuits | Dimensions(mm) | |
|----------|----------------|-------|----------|----------------|-------|
| | A | B | | A | B |
| 2P | 4.19 | 9.40 | 9P | 33.52 | 38.73 |
| 3P | 8.38 | 13.59 | 10P | 37.71 | 42.92 |
| 4P | 12.57 | 17.78 | 11P | 41.90 | 47.11 |
| 5P | 16.76 | 21.97 | 12P | 46.09 | 51.30 |
| 6P | 20.95 | 26.16 | 13P | 50.28 | 55.49 |
| 7P | 25.14 | 30.35 | 14P | 54.47 | 59.68 |
| 8P | 29.33 | 34.54 | 15P | 58.66 | 63.87 |

Beijing Hongli Kunpeng International Trade Co., Ltd.

| | | |
|------|-------|--------|
| Unit | Scale | Sheet |
| mm | 2:1 | 1 of 1 |

Draw BY: Jack Yin
 Approved: GONGYB

Title : 4.19mm PITCH
 SINGLE ROW WAFER

General Tolerance

| | |
|-----------|--------|
| x.xx±0.25 | ANGLE± |
| x.xx≤0.20 | |
| x.xx≤0.15 | |

DRAW NO : HLB-01-WVS-S-XP 59 REV A0

| | | |
|-----|--------------|------------|
| A0 | NEW RELEEASE | 2015.03.11 |
| REV | DESCRIPTION | DATE |