


SEC:A-A



SEC:B-B

Ordering information & Specifications

Unit:mm

Part NO.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
C3030F-TP-D-H	AWG#16-#20	2.20mm(max)	Phosphor Bronze	Tin over Nickel	5,000 PCS
C3030F-GP-D-H	AWG#16-#20	2.20mm(max)	Phosphor Bronze	Gold over Nickel	5,000 PCS
C3030F-TCA-D-H	AWG#16-#20	2.20mm(max)	High conductive copper alloy	Tin over Nickel	5,000 PCS
C3030F-GCA-D-H	AWG#16-#20	2.20mm(max)	High conductive copper alloy	Gold over Nickel	5,000 PCS

REV	DESCRIPTION	DATE
A1	CHANGE THE DRAWING	2021.03.29
A0	NEW RELEASE	2021.02.04

Beijing Hongli Kunpeng International Trade Co., Ltd.

Unit	Scale	Sheet	TITLE
mm	8:1	1 of 1	3.00mm PITCH CRIMP TERMINAL
DRWN	CHK'D	APPR	
Dengchun Yi	Diankui Wan	Jack Yin	
General Tolerances			THIRD ANGLE PROJECTION
x.xx±0.25 x.xxx±0.20 x.xxxx±0.15 ANGLES ±1°			DRAWING NO. HLB-30-F-T-D-H 50
			REV A1