



Ordering Information:

C3030HFE-2x6P - ***
1 2

1.Part NO.

2.Material:

(Blank): Nylon 66,UL94V-0(Black)

GWT: Nylon 66,UL94V-0(Black),IEC 60335-1,5th Edition
Glow Wire Capable.

SPECIFICATIONS:

Current Rating: 9.5A AC,DC

Voltage Rating: 600V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1500V AC/minute

Material: Nylon 66,UL94V-0(Black)

Beijing Hongli Kunpeng International Trade Co., Ltd.

Unit	Scale	Sheet	TITLE
mm	2.5:1	1 of 1	3.00mm PITCH PCI-SIG 12VHPWR H+ HOUSING
DRWN	CHK'D	APPR	
Wenmin Luo	Diankui Wan	Jack Yin	DRAWING NO.
General Tolerances			THIRD ANGLE PROJECTION
x,xx±0.25			
x,xxx±0.20			
x,xxx±0.15			DRAWING NO.
ANGLES ±1°			HLB-30-HFE-2x6P 45
REV	DESCRIPTION	DATE	REV
A0	NEW RELEASE	2022.03.30	A0