



Ordering Information:

C3030WR-F-2xXP - *** - *** - ***
 1 2 3 4

- 1.Part No.
- 2.Size(H):
 (blank):2.00mm
 H30:3.00mm
- 3.Material:
 (blank):Nylon 66 UL94V-0
 LCP:LCP UL94V-0
 GWT:Nylon 66 UL94V-0,GWT 750°C
- 4.Finish:
 (blank):Tin over Nickel
 G:Gold over Nickel(1"U)
 G3:Gold over Nickel(3"U)
 G15:Gold over Nickel(15"U)
 G30:Gold over Nickel(30"U)

SPECIFICATIONS:

Current Rating: 5A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -40°C ~ +105°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 66,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2x1P	---	6.65	4.30	2x7P	18.00	24.65	22.30
2x2P	3.00	9.65	7.30	2x8P	21.00	27.65	25.30
2x3P	6.00	12.65	10.30	2x9P	24.00	30.65	28.30
2x4P	9.00	15.65	13.30	2x10P	27.00	33.65	31.30
2x5P	12.00	18.65	16.30	2x11P	30.00	36.65	34.30
2x6P	15.00	21.65	19.30	2x12P	33.00	39.65	37.30

Beijing Hongli Kumpeng International Trade Co., Ltd.

Unit	Scale	Sheet
mm	3:1	1 of 1
Draw BY:	Approved :	
Tony Su	Jack Yin	

Title :
3.00mm PITCH
90° Dual Row WAFER
 DRAW NO :
HLB-30-WR-F-2xXP 20 REV
 A0

General Tolerance			ANGLE±
A0	NEW RELEASE	2009.05.10	
REV	DESCRIPTION	DATE	x.xx≤0.20
			x.xxx≤0.15