



Ordering Information:

C3030WR-S-F-XP - ^{***}/₂ - ^{***}/₃ - ^{***}/₄

- 1.Part No.
- 2.Size(H):
(blank):2.00mm
H30:3.00mm
- 3.Material:
(blank):Nylon 66 UL94V-0
GWT:Nylon 66 UL94V-0,GWT 750°C
- 4.Finish:
(blank):Tin over Nickel
G:Gold over Nickel(1"U)
G3:Gold over Nickel(3"U)
G15:Gold over Nickel(15"U)
G30:Gold over Nickel(30"U)

SPECIFICATIONS:

Current Rating: 5A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 10mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1500V AC/minute
Pin Material: Brass/Tin over Nickel
Material: Nylon 66,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	3.00	9.65	8P	21.00	27.65
3P	6.00	12.65	9P	24.00	30.65
4P	9.00	15.65	10P	27.00	33.65
5P	12.00	18.65	11P	30.00	36.65
6P	15.00	21.65	12P	33.00	39.65
7P	18.00	24.65			

Beijing Hongli Kunpeng International Trade Co., Ltd.

Unit	Scale	Sheet	Title :
mm	3:1	1 of 1	
Draw BY:	Approved :		
Tony Su	Jack Yin		3.00mm PITCH 90° SINGLE ROW WAFER
General Tolerance			
			DRAW NO : HLB-30-WR-F-XP 19
A0	NEW RELEASE	2017.09.08	
REV	DESCRIPTION	DATE	REV A0

ANGLE±