


Ordering Information:  
 C3030WR-S-F-2xXP - \*\*\* - \*\*\* - \*\*\*  
 1 2 3 4

- Part No.
- Size(H):  
 (blank):2.00mm  
 H30:3.00mm
- Material:  
 (blank):LCP,UL94V-0  
 GWT:LCP,UL94V-0,GWT 750°C
- Finish:  
 (blank):Tin over Nickel  
 G:Gold over Nickel(1"U)  
 G3:Gold over Nickel(3"U)  
 G15:Gold over Nickel(15"U)  
 G30:Gold over Nickel(30"U)



**SPECIFICATIONS:**

Current Rating: 12.5A AC,DC (AWG #18)  
 Voltage Rating: 600V AC,DC  
 Temperature Range: -40°C ~ +105°C  
 Contact Resistance: 10mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstanding Voltage: 1500V AC/minute  
 Pin Material: Brass/Tin over Nickel  
 Material: LCP,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2x1P	---	6.65	4.30	2x7P	18.00	24.65	22.30
2x2P	3.00	9.65	7.30	2x8P	21.00	27.65	25.30
2x3P	6.00	12.65	10.30	2x9P	24.00	30.65	28.30
2x4P	9.00	15.65	13.30	2x10P	27.00	33.65	31.30
2x5P	12.00	18.65	16.30	2x11P	30.00	36.65	34.30
2x6P	15.00	21.65	19.30	2x12P	33.00	39.65	37.30

Beijing Hongli Kunpeng International Trade Co., Ltd.

Unit	Scale	Sheet	TITLE
mm	3:1	1 of 1	3.00mm PITCH RIGHT-ANGLEDUAL ROW WAFER- SMT TYPE
DRWN	CHK'D	APPR	DRAWING NO.
Xu Lei	DianKui Wan	Jack Yin	HLB-30-WR-S-F-2xXP 17
General Tolerances	THIRD ANGLE PROJECTION		REV
x.x±0.25 x.xx±0.20 x.xxx±0.15 ANGLES ±1°			A2

A2	CHANGE THE DRAWING	2022.01.15
A1	CHANGE THE Current Rating	2018.12.19
A0	NEW RELEASE	2009.05.10
REV	DESCRIPTION	DATE