


Ordering Information:  
 C3030WR-S-F-XP - \*\*\* - \*\*\* - \*\*\*  
 1 2 3 4

- 1.Part No.
- 2.Size(H):  
 (blank):2.00mm  
 H30:3.10mm
- 3.Material:  
 (blank):LCP UL94V-0  
 GWT:LCP UL94V-0,GWT 750°C
- 4.Finish:  
 (blank):Tin over Nickel  
 G:Gold over Nickel(1"U)  
 G3:Gold over Nickel(3"U)  
 G15:Gold over Nickel(15"U)  
 G30:Gold over Nickel(30"U)



**SPECIFICATIONS:**  
 Current Rating: 5A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -40°C ~ +105°C  
 Contact Resistance: 10mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstanding Voltage: 1500V AC/minute  
 Pin Material: Brass/Tin over Nickel  
 Material: LCP,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2P	3.00	9.65	7.30	8P	21.00	27.65	25.30
3P	6.00	12.65	10.30	9P	24.00	30.65	28.30
4P	9.00	15.65	13.30	10P	27.00	33.65	31.30
5P	12.00	18.65	16.30	11P	30.00	36.65	34.30
6P	15.00	21.65	19.30	12P	33.00	39.65	37.30
7P	18.00	24.65	22.30				

Beijing Hongli Kunpeng International Trade Co., Ltd.

Unit	Scale	Sheet	Title :
mm	3:1	1 of 1	
Draw BY:	Approved :		
Tony Su	Jack Yin		<b>3.00mm PITCH          90° SINGLE ROW          WAFER - SMT TYPE</b>
General Tolerance			
			DRAW NO :
A0	NEW RELEASE	2009.05.10	
REV	DESCRIPTION	DATE	HLB-30-WR-S-F-XP 16
			REV
			A0
