


Ordering Information:
C3030WV-2xXP - * - ** - **
1 2 3 4

- Part No.
- Style:
(blank):Type 1
2:Type 2
3:Type 3
- Material:
(blank):Nylon 66 UL94V-0
LCP:LCP UL94V-0
GWT:LCP UL94V-0,GWT 750°C
- Finish:
(blank):Tin over Nickel
G:Gold over Nickel(1"U)
G3:Gold over Nickel(3"U)
G15:Gold over Nickel(15"U)
G30:Gold over Nickel(30"U)



SPECIFICATIONS:
Current Rating: 5A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 10mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1500V AC/minute
Pin Material: Brass/Tin over Nickel
Material: Nylon 66,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2x1P	—	6.65	2x7P	18.00	24.65
2x2P	3.00	9.65	2x8P	21.00	27.65
2x3P	6.00	12.65	2x9P	24.00	30.65
2x4P	9.00	15.65	2x10P	27.00	33.65
2x5P	12.00	18.65	2x11P	30.00	36.65
2x6P	15.00	21.65	2x12P	33.00	39.65

Beijing Hongli Kunpeng International Trade Co., Ltd.

Unit	Scale	Sheet
mm	3:1	1 of 1
Draw BY:	Approved :	
LIZQ	GONGYB	

Title :
**3.00mm PITCH
180° Dual ROW
WAFER**

General Tolerance

A1	Modify drawings	2016.05.10	x.xx±0.25	ANGLE±
A0	NEW RELELEASE	2005.05.10	x.xx±0.20	
REV	DESCRIPTION	DATE	x.xxx±0.15	

DRAW NO :
HLB-30-WV-2xXP 13

REV
A1

Unit	Scale	Sheet		
mm	3:1	1 of 1		
Draw BY:	Approved :			
LIZQ	GONGYB			
General Tolerance				
A1	Modify drawings	2016.05.10	x.xx±0.25	ANGLE±
A0	NEW RELELEASE	2005.05.10	x.xx±0.20	
REV	DESCRIPTION	DATE	x.xxx±0.15	