

Ordering Information:

C3030WV-S-F-2xXP - *** - *** - ***
 1 2 3 4

1.Part No.

2.Size(H):

(blank):2.00mm

H30:3.00mm

3.Material:

(blank):LCP UL94V-0

GWT:LCP UL94V-0,GWT 750°C

4.Finish:


(blank):Tin over Nickel

G:Gold over Nickel(1"U)

G3:Gold over Nickel(3"U)

G15:Gold over Nickel(15"U)

G30:Gold over Nickel(30"U)



SPECIFICATIONS:

Current Rating: 12.5A AC,DC (AWG #18)

Voltage Rating: 600V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1500V AC/minute

Pin Material: Brass/Tin over Nickel

Material: LCP,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2x1P	----	6.65	4.30	2x7P	18.00	24.65	22.30
2x2P	3.00	9.65	7.30	2x8P	21.00	27.65	25.30
2x3P	6.00	12.65	10.30	2x9P	24.00	30.65	28.30
2x4P	9.00	15.65	13.30	2x10P	27.00	33.65	31.30
2x5P	12.00	18.65	16.30	2x11P	30.00	36.65	34.30
2x6P	15.00	21.65	19.30	2x12P	33.00	39.65	37.30

Beijing Hongli Kungpeng International Trade Co., Ltd.

Unit	Scale	Sheet	TITLE
mm	3:1	1 of 1	3.00mm PITCH VERTICAL DUAL ROW WAFER - SMT TYPE
DRWN	CHK'D	APPR	
Xu Lei	DlanKul Wan	Jack Yin	
General Tolerances		THIRD ANGLE PROJECTION	DRAWING NO.
x.x±0.25	x.xx±0.20		HLB-30-WV-S-F-2xXP 5
x.xxx±0.15	ANGLES ±1°		REV A1

REV	DESCRIPTION	DATE
A3	CHANGE THE DRAWING	2022.01.14
A2	CHANGE THE Current Rating	2018.12.26
A1	Update drawings	2011.12.14
A0	NEW RELEASE	2009.05.10