



P.C.B LAYOUT

SPECIFICATIONS:

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -40°C ~ +105°C
 Contact Resistance: 30mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 650V AC/minute
 Material: Nylon 66,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2x2P	2.00	4.80	2x10P	18.00	20.80
2x3P	4.00	6.80	2x11P	20.00	22.80
2x4P	6.00	8.80	2x12P	22.00	24.80
2x5P	8.00	10.80	2x13P	24.00	26.80
2x6P	10.00	12.80	2x14P	26.00	28.80
2x7P	12.00	14.80	2x15P	28.00	30.80
2x8P	14.00	16.80	2x16P	30.00	32.80
2x9P	16.00	18.80			

Beijing Hongli Kunpeng International Trade Co., Ltd.

Unit mm	Scale 3:1	Sheet 1 of 1	Title : 2.00mm Pitch Housing	
Draw By: Diankui Wan		Approved : Jack Yin		
General Tolerance			DRAW NO : HLB-11-H-2xXP 1	
x.x±0.25 x.xx±0.20 x.xxx±0.15				
PROJECT 				
REV	DESCRIPTION	DATE	REV A0	

A0	NEW RELEASE	2019.12.23
REV	DESCRIPTION	DATE