



SPECIFICATIONS:

Current Rating: 2A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -40°C ~ +105°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Material: PBT,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2x2P	2.00	4.35	2x5P	8.00	10.35
2x3P	4.00	6.35	2x6P	10.00	12.35
2x4P	6.00	8.35			

Beijing Hongli Kumpeng International Trade Co., Ltd.

Unit mm	Scale 6:1	Sheet 1 of 1
Draw BY: Tony Su	Approved : Jack Yin	

Title :
2.00mm Pitch
Dual Row Housing

REV	DESCRIPTION	DATE	General Tolerance	ANGLE±
A1	CHANGE THE DRAWING	2017.04.02	x.x≤0.25	
A0	NEW RELEASE	2012.06.19	x.xx≤0.20	
			x.xxx≤0.15	

DRAW NO :
HLB-05-HB-N-2xXP-B 113 REV
A1