



SPECIFICATIONS:

Current Rating: 2A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -40°C ~ +105°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Material: Nylon 66 +25%GF, UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2x2P	2.00	4.35	2x5P	8.00	10.35
2x3P	4.00	6.35	2x6P	10.00	12.35
2x4P	6.00	8.35			

Beijing Hongli Kunpeng International Trade Co., Ltd.

Unit	Scale	Sheet
mm	6:1	1 of 1
Draw BY:	Approved :	
Tony Su	Jack Yin	

Title :
 2.00mm Pitch
 Dual Row Housing

A1	CHANGE THE DRAWING	2017.03.01	x.x≤0.25 x.xx≤0.20 x.xxx≤0.15	ANGLE±
A0	NEW RELEESE	2012.06.19		
REV	DESCRIPTION	DATE		

DRAW NO :
 HLB-05-HB-N-2xXP-C 112
 REV A1