



SPECIFICATIONS:
 Current Rating: 2A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -40°C ~ +105°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Material: PBT,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2x7P	12.00	14.35	8.00	2x17P	32.00	34.35	28.00
2x8P	14.00	16.35	10.00	2x18P	34.00	36.35	30.00
2x9P	16.00	18.35	12.00	2x19P	36.00	38.35	32.00
2x10P	18.00	20.35	14.00	2x20P	38.00	40.35	34.00
2x11P	20.00	22.35	16.00	2x21P	40.00	42.35	36.00
2x12P	22.00	24.35	18.00	2x22P	42.00	44.35	38.00
2x13P	24.00	26.35	20.00	2x23P	44.00	46.35	40.00
2x14P	26.00	28.35	22.00	2x24P	46.00	48.35	42.00
2x15P	28.00	30.35	24.00	2x25P	48.00	50.35	44.00
2x16P	30.00	32.35	26.00				

Beijing Hongli Kungpeng International Trade Co., Ltd.

Unit	Scale	Sheet
mm	4:1	1 of 1
Draw By:	Approved :	
Dlankul Wan	Jack Yin	

Title :
 2.00mm Pitch
 Dual Row Housing

REV	DESCRIPTION	DATE	General Tolerance
A2	CHANGE THE DRAWING	2019.02.16	x.xx±0.25 x.xxx±0.20 x.xxxx±0.15
A1	MODIFY THE MOLD	2017.04.02	
A0	NEW RELEASE	2011.01.05	

PROJECT		DRAW NO : HLB-05-HB-N-2xXP-D 110	REV A2
---------	--	--	------------------