



REV	DATE	DESCRIPTION
B	2023.11.6	

MATERIAL:
 Housing: PBT UL 94V-0
 Contacts: Brass
 ELECTRICAL:
 Current rating: 2A
 Contact resistance: 30mΩ max
 Insulator resistance: 1000 MΩ min
 Dielectric withstanding voltage: 1000V AC
 Operating temperature: -55° C to +125° C

HLAL - * 5 * * * * P B
 1: 2.54mm 2: 5.08mm
 Position: 30 20 15 10 5
 Dip Length: X (mm)
 1: 4.0 2: 13.0 3: 15.0 4: 17.0 5: 25.0
 B(Blank): without lock
 D: DIP
 00: G/F 02: 2u" 03: 3u"
 05: 5u" 10: 10u" 15: 15u" 30: 30u"
 C: Dip Tin Contact Gold
 G: Gold

Pitch	Position	Rows with Contacts	Contact Arrange
2.54mm	30	a b c	
	20	a b -	
	20	a - c	
5.08mm	10	a - -	
	15	a b c	
	10	a b -	
	10	a - c	
5	a - -		

UNIT : mm

Beijing Hongli Kunpeng International Trade Co., LTD	MODEL NAME:	SELECT	1	2	3	EXTRA	PART NO. HLAL- *2***DB	
	DIN41612 330 Straight female DIP Traditional type without harpoon	DIM TOL	0.000	0.05	0.05	0.10	APPROVED BY:	FILE NO. D1N076-30DB
			0.00	0.10	0.15	0.20	CHECKED BY:	SCALE:
			0.0	0.15	0.25	0.30	DRAW BY: jenny	DATE : 2010-6-18
			0.	0.25	0.30	0.40		
		ANGLE	1.0°	3.0°	5.0°			