



REV	DATE	DESCRIPTION
B	2023.11.7	

MATERIAL:
Housing: PBT UL 94V-0
Contacts: Brass
ELECTRICAL:
Current rating: 2A
Contact resistance: 30mΩ max
Insulator resistance: 1000 MΩ min
Dielectric withstanding voltage: 1000V AC
Operating temperature: -55° C to +125° C

HLAL - * 5 * * * * P B
3: 2.54mm 4: 5.08mm
5: Female straight (Easy Type)
Position:
64 32 16
Dip Length: Y (mm)
1: 5.3 3: 15.0 4: 13.0 5: 17.0 7: 25.0
B (Blank): without lock
P: Press Fit
00: G/F 02: 2u" 03: 3u"
05: 5u" 10: 10u" 15: 15u" 30: 30u"
C: Dip Tin Contact Gold
G: Gold

Pitch	Position	Rows with Contacts	Contact Arrange
2.54mm	64	a b	
	32	a -	
5.08mm	32	a b	
	16	a -	

UNIT : mm

Beijing Hongli Kunpeng International Trade Co., LTD	MODEL NAME:	DIN41612 264 Fish eye female without harpoon	SELECT	1	2	3	EXTRA	PART NO. HLAL- * 5 * * * * P B	
			DIM	0.000	0.05	0.05	0.10	APPROVED BY:	FILE NO. DIN085-64PB
				0.00	0.10	0.15	0.20	CHECKED BY:	SCALE:
				0.0	0.15	0.25	0.30	DRAW BY: jenny	DATE : 2020-12-28
				0.	0.25	0.30	0.40		
			ANGLE	1.0°	3.0°	5.0°			